CE IP65 | IK08

HIGH EFFICIENCY CONTROLLER

LiFePO4 BATTERY

LED
HIGH QUALITY LED

IP65

streetleaf®

PATH
Spec Sheet

RELIABLE LIGHTS. **RENEWABLE POWER**

Streetleaf PATH is a fully off-grid solar bollard designed to deliver reliable pedestrian lighting for paths, walkways and outdoor spaces.

APPLICATIONS



- Building Perimeters
- Commercial Landscapes
- Parking Areas
- Parks
- Plazas
- Trails
- Walkways

PHYSICAL PARAMETERS

Dimensions of Bollard	**L** 16.1 in (410 mm) **W** 12.0 in (306 mm) **H** 42.5 in (1080 mm)
Net Weight of Bollard	~40 lbs
IK Rating	IK08
Warranty	1 year



LED LIGHTHEAD

Light Output	3 W
Typical Luminous Flux	500 lm
Color Temperature	2700 K
Operating Voltage	12V
Light Distribution	Type V

SOLAR PANELS

Power of PV Module	50 W
Solar Panel Technology	Rigid Monocrystalline Silicon

BATTERY

Battery Capacity	192 Wh
Battery Chemistry	LiFePO4
Battery Autonomy	4 days

ENVIRONMENTAL REQUIREMENTS

Charge Temp. (day)	32°F (0°C) to 131°F (55°C)
Discharge Temp. (night)	-4°F (-20°C) to 140°F (60°C)
Storage Temp.	59°F (15°C) to 95°F (35°C)

MOUNTING

Installation Type	Surface Mount
Recommended Installation Distance	15 ft
Recommended Surface Types	Concrete, Wood, Composite Decking

Rev09102026

streetleaf
813.800.LEAF (5323)
www.streetleaf.com

FLORIDA
2502 N. Rocky Point Dr.
Ste 1070,
Tampa, FL 33607

GEORGIA
800 Battery Ave SE
Ste 300,
Atlanta, GA 30339

TEXAS
201 West Street
16th Floor,
Austin, TX 78701